

## Oakville Forklift Training Course

Oakville Forklift Training Course - OSHA and CSA establish criteria for forklift safety training that meets current regulations and standards. Anybody intending to operate a forklift is needed to successfully complete safety training prior to making use of any type of forklift. The accredited Forklift Operator Training Program is intended to offer individuals training with the practical skills and knowledge to become an operator of a forklift.

There are forklift operation safety rules that must be followed pertaining to pre-shift inspections, and regulations for lifting and loading.

Prior to a shift starting, an inspection checklist has to be done and given to the Instructor or Supervisor. If whichever maintenance issue is discovered, the equipment should not be utilized until the issue is dealt with. To indicate the equipment is out of order, the keys need to be removed from the ignition and a warning tag placed in a spot which is seen.

Loading safety rules consist of checking the rating capacity on the forklift nameplate and determining if the weight of the load falls within capacity. The forklift forks should be in the downward position when the forklift is starting up. Don't forget that there is a loss of around 100 pounds carrying capacity for every one inch further away from the carriage that the load is carried.

Lifting must begin with the driver moving to a stopped position about three inches from the load. The mast should then be leveled until it has reached a right angle with the load. Raise the forks to one inch beneath the slot on the pallet and drive forward. Next lift forks four inches. Tilt back the load to secure it for moving. Drive the lift backwards if the load obscures frontal vision. Check behind and honk to warn other employees. Do not allow forks to drag on the ground.

The load should be loaded by the forklift in such a way that ensures the load is secure and will not create a danger to other people or objects. Restraining loads is needed for materials which could shift during transport and destabilize the forklift.

Drums can be strapped together so as to avoid movement and shifting of the drums. Forklift operators must drive slowly when lifting liquids, to lessen instability in the forklift.